


GOOLOO
Welcome Guide

Multi-function Car Jump Starter
GP37
Manual





www.gooloo.com

Please read carefully before using it and please keep it in a safe place for you may need in future.



1

Product Layout

2

Operation Guidance

Indicator Light:

Press the switch to check the storage level:


Indicator	1 Flashing	1 Solid	2 Solid	3 Solid	4 Solid
Storage Level	0%	25%	50%	75%	100%

The indicator light will flash one by one during the period of charging. Different numbers of solid indicators show different storage level of GP03. All indicators light will go off automatically, when the charging is paused or completed.

How to Charge

1. Charged By Home Adaptor

1. Plug the home adaptor into the universal socket.
2. Connect 15V 1A input port of E-Power to the other end of home adaptor.



3

2. Charged By Car

1. Plug the car adaptor into the socket of cigarette lighter.
2. Connect the other end of home adaptor to the 15V/1A input port.



How to Jump Start a Vehicle

Make sure it is over 60% charged. If have not use it more than two months, should charge it first.



1. Connect the smart cable plug to jump starter
2. Red clamp connect "+", black clamp connect "-"
3. Start the vehicle
4. Remove the plug from the jump starter
5. Remove the clamp from the battery

4

How to Use the Smart Cable

Connect the blue plug fully seated into the host, and make sure the Cable Indicator is off.



Operate following the instruction of the Cable Indicator:

1. Green Light On: The connection is correct and the circuit is working, you can turn on the engine to boost directly.
2. Red Light On with Buzzing: The connection is wrong, **DO NOT** start the engine, and must reconnect it properly as step2 mentioned above until the Green Light light.
3. Green Light Blinking with Buzzing: The vehicle battery is low, press the "BOOST" button, wait for the Green Light stability, then start the engine within 30s.





5

4. No Lights on, No buzzing: The vehicle's battery maybe damaged, confirm the clamps connection, press the "BOOST" button, wait for the Green Light stability, then start the engine within 30s.



How to Charge your Device

1. Plug the switch cable to 5V /2A USB output port.
2. Select the appropriate connector for your device, GPower100 can identify and charge it automatically. The indicators light will lighting when charging.



How to Charge 19V Notebook

1. Plug the switch cable A to USB 19V 3.5A output port.
2. Select appropriate connector for your Notebook and connect it to the switch cable A and your Notebook.

6

3. Press the switch button to charge/power supply.



How to Switch the LED Light

Press the LED Flash Light Switch seconds to turn on it, press slightly to switch 3 lighting mode: Flash light, Strobe light, SOS Signal flash. Turn off the light also use this switch.

Parts List

#	Parts Name	Quantity
1	Host	1
2	Cable A (Micro USB, Type-C, Apple)	1
3	Cable B (for Notebook)	1
4	Notebook Connector	8
5	Home Adapter	1
6	Car Adapter	1
7	Smart Jump Cable	1

7

Technical Specification

Input:	15V/1A
Output:	5V/2A;5V/1A;19V/3.5A;12V/10A
Capacity:	15000mAh
Start Current:	300A
Peak Current:	600A
Size:	157*75*36(mm)
Weight:	540g
Operating Temp.	-20℃~60℃/-4℉~140℉
Lifetime	>1000 cycles
Full Charging Time:	5 Hours

Trouble Shooting

Finding	Cause	Remedies
GOOLOO GP37 is still not full charged while its 5 indicator lights are solid.	60% Charging for longer storage when no usage.	Unplug the adaptor and plug it again.
No response when pressing the switch button.	Low voltage protection is started.	Plug the adapter into 15V/1A input port to activate the device.

8

FAQ

Q1: What cars are GOOLOO® GP37 compatible with?
A: Gas engines up to 6.5L/V8 or diesel engines up to 5.5L.

Q2: What is GOOLOO® GP37 operating temperature and how to store it?
A: The car jump starter GOOLOO® GP37 is lithium-ion, operating temperature is -20~60℃/-4~140℉, if the ambient temperature is higher than 60℃/140℉, the internal instruction of lithium-ion cells will be changed, it may swell and will be unsafe. So DO NOT store it in car for long time, especially in summer.

Q3: How to jump start a car with GP37?
A: 1). Make sure it is over 60% charged. If have not use it more than two months, should charge it first.
2). Turn on it and connect the red clamp to "+", the black clamp to "-" end of the car battery.
3). When the jump cable indicator turns green (make sure), start your car.
4). If the jumper cable indicator does not turn green, turn on the car headlight and wait the indicator turns green, try again to

9

start the car.
5). Unplug the jumper cables from the jump starter within 30 seconds, and remove the clamps from your car battery.

Q4: What is the correctly connected of the GP37 and the car?
A: When the clamps connected to car battery, the jumper cable indicator light shines a steady green light, is the correctly connected. If the light flash red, it's wrong connected.

Q5: What should I do if GOOLOO® GP37 cannot start a car?
A: Recharge and fully charged it, try it again, make sure to wait 10 seconds between each jump attempt. If it still not works, email us: fiona@gooloo.co, or contactus@gooloo.com, within 18 months warranty period (Attach your order ID, it is necessary)

Q6: What should I do if the GOOLOO® GP37 cannot be charged?
A: Charge it with both a 15V wall charger and car charger, wait for about whole night. If it still not works, email us: fiona@gooloo.co, or contactus@gooloo.com,

10

within 18 months warranty period (Attach your order ID, it is necessary)

Q7: What should I do if GOOLOO® GP37 cannot charge other devices?
A: Using a different charging cable to charge again, if it can work, must the cable defective, email us we will provide you a new cable, if is still not work, email us: fiona@gooloo.co, or contactus@gooloo.com, within 18 months warranty period (Attach your order ID, it is necessary)

Q8: Can the GOOLOO® GP37 charge other devices while it is being charged?
A: Yes.

Q9: Can GOOLOO® GP37 charges other devices while starting a car?
A: No.

Q10: If there is no response when pressing the switch button of GOOLOO® GP37, how can I do?
A: Maybe it is cause by low voltage protection Plug the adaptor into the 15V/1A input port to activate.

11

Q11: How long the storage of battery will remain?
A: 6-12 months, however, we suggest to recharge it every 3 months.

Toxic and Harmful Substances


Composition and amount of toxic or harmful substance in GP37					
Pb	Hg	Cd	Cr(VI)	PBB	PBDE
0	0	0	0	0	0

Indicate that the content of harmful substances in all homogeneous materials is all lower than the prescribed limit of MCV (the standard 2002/95/EC/RoHS)

12

Attention

- Do Not Submerge In Water
- Do Not Disassemble
- Do Not Dropping
- Advoid Extreme Temperatures
- Do Not Place Near or Into Fire



13

Customer Service

18-Month Limited Warranty

Lifetime Technical Service

Feel Free to Contact Us

fiona@gooloo.co
contactus@gooloo.com

For FAQ and More Information

www.gooloo.com

- @gooloofans
- @+Gooloofans
- @gooloo-tech
- @GoolooOfficial
- @mygooloo
- gooloo

14

GOOLOO

Thank You for Choosing !

Made in China
Product Serial Code: 16/ GP37/A